

SUPERLITE REGULATIONS

Superlite class will exist for 'formula' type machines. The class listed below (1-1 to 1-5) allows modifications to the machines to be carried out while still keeping a similar level of performance between machines.

These rules apply to all National Championship and Endurance Championship races. At other meetings these rules will apply unless varied in the Supplementary Regulations.

- 1 Capacity Groups:
(Refer to rule 5 below for specifications and restrictions within a capacity group)
- 1.1 Multi-cylinder four Stroke up to 450cc
- 1.1a the working displacement of a 3 or 4 cylinder 4 Stroke (cylinders producing power) shall be no more than 450cc.
- 1.2 Multi-cylinder production based two strokes up to 400cc
- 1.3 Twin cylinder, air cooled, four stroke up to 750cc
- 1.4 Single cylinder four stroke 251cc - Open Capacity
- 1.5 Single cylinder two stroke 200cc - 500cc
- 1.6 Twin cylinder, 2 or more valves, water cooled 4 Stroke up to 650cc
- 2 Number Plate Colours and placement:
Refer to rule 10.2.3
- 3 Fuel:
Refer to rule 10.17.2
- 4 Machine Specifications (General):
All machines must comply with the relevant General Competition Rules such as Chapter 10. Machines with re-bored cylinders must remain within the appropriate capacity limit.
- 4.1 Multi-cylinder four stroke machines eligible under rule 1.1 shall only be limited to the capacity, and fuel requirements above.
- 4.2 The specifications for up to 400cc two stroke Production based machines eligible under 1.2 are described in rule 5.
- 4.3 Twin cylinder four strokes shall be limited as follows:
 - a) Up to 500cc, no restrictions apart from fuel as above.
 - b) Over 500cc, two valves per cylinder are restricted to 750cc and must be air cooled, fuel as per rule 3,

- c) Over 500cc, two or more valves per cylinder and water cooled are restricted to 650cc, fuel as per rule 3. Additionally these machines must retain the standard OEM air box/cleaner assembly in its entirety, air filter element and carburettor (with the exception of removable jets or throttle body, including injector).
- 4.4 Single cylinder four stroke machines eligible under rule 1.4 shall only be limited to the fuel requirements as per rule 3. Capacity is unrestricted.
- 4.5 Single cylinder two stroke machines eligible under rule 1.5 shall be limited to the capacity and fuel requirements as per rule 3.
- 4.6 Be fitted with clip-on style bars (no MX, Motard, and Enduro or trail/dual purpose style of handle bars)
- 5 Specifications for up to 400cc two stroke production based machines:
The machine must be based on a production motorcycle. No homologation is necessary however the Road Race Commission or Technical Steward shall have the power to rule whether or not a machine is eligible.
- 5.1 Capacity:
Must not exceed 400cc. Machines with re-bored cylinders must remain within the capacity limit.
- 5.2 Engine Specifications:
 - a) The crankcase must be from the original road going motorcycle. The manufacturer's identification marks must be retained, and may be examined to ensure compliance. But may be modified without any further restriction.
 - b) Any aftermarket or race piston and ring set may be fitted provided the cylinder remains within the capacity limit.
 - c) The original carburettor may be replaced by any brand or type
- 6 Modifications permitted:
Provided all the previous requirements are met and the machine complies with the relevant General Competition Rules, all other items are unrestricted
- 6.1 Quick shifters may be used
- 6.2 Lap timing and data logging equipment is allowed